



*WE'RE NOT JUST CREATING REMOTE CONTROLS,  
WE'RE CREATING A SAFER WORKPLACE.*

RX MFSHL DC8/16

## Product Information

### RX MFSHL DC8/16

#### Standard Features:

- MFSHL Functionality
- Lightweight and Portable Package
- Fully Programmable via H-Link
- External Antenna
- Diagnostic LED's

#### Typical Applications:

- Chain Hoists
- Small Overhead Cranes
- Conveyor Systems
- Monorails
- Hook Loaders
- Concrete Mixers
- Tow Trucks
- Tailgates
- Several other applications





RX MFSHL DC8/DC16 Specifications:					
Housing Material:	Polycarbonate (PC) blend or HSP 32	Weight:	DC8 245gr (0.5lbs)	DC16 PWM 260gr (0.6lbs)	DC16 2.4GHz 570gr (1.3lbs)
Environmental Protection:	IP 65 (Exceeds Nema 12/13)	Dimensions:	DC8 H:148mm (5.8") D:118mm (4.7") D:36mm (1.4")	DC16 PWM 148mm (5.8") 118mm (4.7") 36mm (1.4")	DC16 2.4G 131mm (5.2") 165mm (6.5") 65mm (2.6")
Antenna:	External	Power Supply:	12/24 VDC +/- 20%		
LED Diagnostics:	3 LEDs indicate operation, reception, program mode and error	Frequency Range:	868MHz, 915MHz, 2.4GHz		
RX-MFSHL DC8 Outputs:	7 N.O. solid state switching outputs at 3A per output All outputs must total less than Main-Contact 8A maximum	Typical Operating Range:	Approximately 30m (100ft.) line of sight		
RX-MFSHL DC16 PWM Outputs/ Inputs:	15 Solid state on/off outputs at 2A N.O./N.C. and on/off delays free Programmable 2 PWM Outputs 2 DC inputs All digital and PWM outputs must total less than Main-Contact 8A maximum	Safety:	Active and passive Stop function Parity & Checksum		
		Safety Address:	20-bit (over 999,999 individual possibilities) Permanently assigned in transmitter Address Module (ADMO)		
RX-MFSHL DC16 2.4GHz Outputs/ Inputs:	15 Solid state on/off outputs at 2A N.O./N.C. and on/off delays free Programmable 2 PWM Outputs 4 Digital and 4 Analogue Inputs 1 5VDC Output All digital and PWM outputs must total less than Main-Contact 8A maximum	Standard Features:	Fully programmable via PC with H-Link modem; Built-in quick disconnect connector; Built-in warning device (horn) @ 96dB output; Main Contact (MC) short-circuit monitor protection		
RF Unit:	Type MFS with single frequency, selectable duty cycle	Temperature Range:	-20°C + 70°C (-4°C + 158°F)		
Standard Options:	Wall mount plug receptacle, including connector; Cable backup;	Humidity Range:	0 - 97% maximum non-condensing		
Baud Rate:	Antenna extension Up to 76.8 Kbps. (selectable via H-Link)	Response Time:	Approx. 100 msec.		

#### ABOUT HETRONIC:

Since 1982 Hetronic Inc. has manufactured and delivered over 500,000 radio remote control systems to customers around the world. We are recognized leaders in providing the safest, most reliable industrial Safety Radio Remote Control (RRC) user interface solutions for process and equipment control applications. Every Hetronic system is designed and configured to customer specific application needs for safety, performance, reliability and productivity. With a global network of service locations in over 50 countries operators can count on Hetronic to be there when they need local and immediate service and support. Hetronic is committed to deliver turnkey radio remote control solutions that not only meet the highest standards for RF communication, but that also provide you with the newest technology and highest possible value to get the job done efficiently and safely in the harshest of environments.

Contact a Hetronic expert and learn more at [www.hetronic-canada.com](http://www.hetronic-canada.com)

