



*WE'RE NOT JUST CREATING REMOTE CONTROLS,
WE'RE CREATING A SAFER WORKPLACE.*

RX DC-MOBILE

Product Information

RX DC-MOBILE

Standard Features:

- Light Weight
- Portable
- Capable of operating at a wide range of frequencies
- IP65

Typical Applications:

- Material Handling
- Overhead Cranes
- Work Platforms
- Container Handling
- Specialty Applications



RX DC-MOBILE Specifications:			
Housing:	Impact resistant polymer composite	Weight:	620gr (1.4lbs)
Environmental Protection:	IP 65 (Exceeds Nema 12/13)	Dimensions:	H: 131mm (5.2") W: 165mm (6.5") D: 65mm (2.6")
Antenna:	External via TNC connector		
Fuse:	20A mini blade type	Power Supply:	12 - 24 VDC +/- 20%
Inputs:	1 Proportional output limit input at 0/3.3-36 VDC 4 Programmable analog/digital inputs (analogue at 0-5 VDC digital at 0/3.3 – 36VDC)	Frequency Range:	4xxMHz, 8xxMHz, 9xxMHz, 2.4GHz
Outputs:	4 Programmable PWM/actuator motor/digital outputs 1 MC on/off output at 12/24 VDC, 10 A maximum load 6 Programmable on/off outputs at 12/24 VDC, 8 A sourced by MC output 3 Programmable on/off outputs at 12/24 VDC, 8 A externally sourced, GND side switching capable 1 +5 VDC, 500 mA e-fused supply output	Typical Operating Range:	Up to 100m (300ft) for <=1GHz; Up to 30m (131ft) for 2.4GHz
		Temperature Range:	-20°C + 70°C (-4°F + 158°F)
RF Unit:	Type CS synthesized with multiple frequencies	Humidity Range:	0 - 97% maximum non-condensing
Safety:	20-bit address scheme with up to 1 million possibilities; Active and passive Stop function; Parity and Checksum; Safety Category 3 Compliant	Response Time:	Less than 100 msec.
Standard Features:	Fully programmable via H-Link Built-in quick disconnect connector; RS232 cable backup capable; Auto hold of proportional and digital outputs; Quick set programming of proportional outputs; Up to 4 transmitters can control 1 receiver; Vibration mounts	Baud Rate:	Up to 9600 Kbps
		Diagnostics:	External LEDs, power/operation, TX signal reception, E-stop error, TX signal type.

ABOUT HETRONIC:

Since 1982 Hetronic Inc. has manufactured and delivered over 500,000 radio remote control systems to customers around the world. We are recognized leaders in providing the safest, most reliable industrial Safety Radio Remote Control (RRC) user interface solutions for process and equipment control applications. Every Hetronic system is designed and configured to customer specific application needs for safety, performance, reliability and productivity. With a global network of service locations in over 50 countries operators can count on Hetronic to be there when they need local and immediate service and support. Hetronic is committed to deliver turnkey radio remote control solutions that not only meet the highest standards for RF communication, but that also provide you with the newest technology and highest possible value to get the job done efficiently and safely in the harshest of environments.

Contact a Hetronic expert and learn more at www.hetronic-canada.com

